

Microwave Precision

Fixed Attenuator

RCAT-SERIES

50Ω 2W DC to 20 GHz

The Big Deal

- Exceptional power handling of 2W
- Wide band width DC to 20 GHz
- Miniature size 2.25 mm x 2.25 mm x 1.1 mm Ceramic package
- Highly reliable and repeatable performance



Product Overview

RCAT attenuators are fixed value absorptive attenuators. The highly precision and repeatable monolithic attenuator chip is processed using the most advanced semiconductor processing techniques. The Cu filled through-die via's and Cu metallization on the backside provides a very low thermal resistance path to dissipate the attenuated power. The attenuator chip is packaged in an LTCC hermetic package utilizing fully automated and highly reliable manufacturing processes.

Key Features

| Feature | Advantages |
|--------------------------|--|
| Max power input 2W | Thermally optimized design can operate reliably at much higher input power as compared to similar devices |
| Band width DC to 20 GHz | Supports a broad band of applications with predictable and repeatable performance, excellent choice to buffer cascaded reflective components. |
| Ceramic Hermetic package | Highly reliable hermetic package provides predictable and repeatable performance in military applications including ground, air, and ship requirements |
| Very Small Size | Miniature 2.25 mm x 2.25 mm and very low profile of 1.1 mm. |



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine  Provides ACTUAL Data Instantly at minicircuits.com

For detailed performance specs & shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Microwave Precision Fixed Attenuator

RCAT-02+

50Ω 2W 2dB DC to 20 GHz

Product Features

- fixed value, absorptive device
- wide bandwidth, DC-20 GHz
- excellent attenuation accuracy & flatness
- miniature size 2.25 mm x 2.25 mm x 1.1 mm
- ceramic, hermetic, nitrogen filled
- aqueous washable

Typical Applications

- cellular
- PCS
- communications
- radar
- wideband military
- test and measurement equipment




CASE STYLE: LZ1737
PRICE: \$4.95 ea. QTY. (20)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

General Description

RCAT-02+ (RoHS compliant) is a wideband fixed attenuator with excellent attenuation accuracy and flatness. It can handle up to 2W. The integrated circuits comprising of thin film resistors is bonded in an optimized multi layer integrated LTCC substrate, and then hermetically sealed under a controlled nitrogen atmosphere with gold-plated covers and eutectic AuSn solder. These amplifiers have been tested to MIL requirements for gross leak, fine leak, thermal shock, vibration, acceleration, mechanical shock, and HTOL.



Pad Description

| Function | Pad Number | Description |
|----------------|------------|-----------------------------|
| RF IN / RF-OUT | 1 | RF input / output pad |
| RF-OUT / RF IN | 3 | RF output / input pad |
| GND | 2,4 | Connected to circuit ground |



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 *The Design Engineers Search Engine* Provides ACTUAL Data Instantly at minicircuits.com

For detailed performance specs & shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.



REV. OR
M141419
RCAT-02+
BT/CP/AM
130424
Page 2

Electrical Specifications¹ at 25°C, 50Ω

| Parameter | Condition (GHz) | Min. | Typ. | Max. | Unit |
|-----------------|-----------------|------|------|------|------|
| Frequency Range | | DC | — | 20 | GHz |
| Attenuation | 1 | 1.5 | 2.04 | 2.5 | dB |
| | 10 | 1.9 | 2.37 | 2.9 | |
| | 20 | 1.9 | 2.73 | 3.5 | |
| Return Loss | 1 | — | 30 | — | dB |
| | 10 | — | 18 | — | |
| | 20 | — | 16 | — | |

Typical Performance Data at 25°C

| Frequency (GHz) | Attenuation (dB) | Return Loss (dB) |
|-----------------|------------------|------------------|
| 0.05 | 2.02 | 39.68 |
| 2.00 | 2.07 | 25.08 |
| 5.00 | 2.20 | 18.35 |
| 8.00 | 2.32 | 16.92 |
| 10.00 | 2.37 | 18.13 |
| 12.00 | 2.39 | 21.46 |
| 15.00 | 2.46 | 29.46 |
| 17.00 | 2.58 | 20.99 |
| 19.00 | 2.64 | 16.67 |
| 20.00 | 2.73 | 15.89 |



Absolute Maximum Ratings²

| | |
|---|----------------|
| Operating Case Temperature ³ | -55°C to 125°C |
| Storage Temperature | -65°C to 150°C |
| RF Input Power ⁴ | 2W at 25°C |

1. Tested using characterization test circuit as defined in Figure 1. See graphs and data above for performances at all other frequencies.
2. Permanent damage may occur if any of these limits are exceeded.
3. Case is defined as ground lead.
4. RF Power at 25°C case temperature: 2W. Derate linearly to 0.33W at 125°C.

Characterization Test Circuit





Fig 1. Block diagram of Test Circuit used for characterization. Characterization was performed by Modelithics®, conditions test board details are available at: <http://www.modelithics.com/datasheet2/606.pdf>

Product Marking



Additional Detailed Technical Information

additional information is available on our dash board. To access this information [click here](#)

| | |
|--|--|
| Performance Data | Data Table |
| | Swept Graphs |
| Case Style | LZ1737 Ceramic package, Terminal finish: Ni-Pd-Au |
| Tape & Reel Standard quantities available on reel | F108 7" reels with 20, 50, 100, 200, 500, 1K or 2K devices. |
| Suggested Layout for PCB Design | click here |
| Evaluation Board | TB-668-02+ |
| Environmental Ratings | ENV-71 |

ESD Rating

Human Body Model (HBM): 250V, Class 1A (JESD22-A114)

Machine Model (MM): 200V, Class B (JESD22-A115)

MSL Rating

Moisture Sensitivity: MSL1 in accordance with IPC/JEDEC J-STD-020D